



IntelliCut Series Two

NC Hydraulic Guillotines

IntelliCut delivers quality you can trust and shearing performance you can rely on.

Our Series 2 range is designed to deliver maximum value with robust build quality and great features.

IntelliCut Series Two 10mm x 3200mm specifications:

Model	Cutting capacity (mm)	Cutting length (mm)	Cutting angle	Backgauge reach (mm)	Backgauge speed (mm / sec)	No. of hold-down pads	Motor power (kw)	Weight (kg's)	Dimensions (mm)
10mm/3200	10mm	3200	2°	20 - 750	150	14	11	8000	3860 x 1700 x 1700

- Control: Estun E21-S control 40 programs, 25 steps per program.
- Electrics: Schneider.
- Seals: NOK seals (Japan).
- Motor: Siemens motor.
- Pump: USA made gear pump.
- Hydraulics: Bosch Rexroth valves.
- Backstops: Automatic, motorised running on ballscrews with linear guides.
- Blade gap: Manual adjustment.
- Shadow cutting line.
- Foot pedal: Heavy duty with emergency stops.
- Material support: Side squaring arm and front supports with flip over stops and squaring discs.
- Material handling: Rollers on table for smooth material handling.
- Material ejection: Rear slider plates for material.
- Movement: Single and continuous stroke.
- Front safety: Front blade guards with safety micro switches.
- Rear safety: Side guards with light curtain and emergency safety stop.
- Guarantee: 12 months parts and labour, see terms and conditions of sale.